



Fire Apparatus Order Detail:

Quotation Number: 69655 Shop Order Number: 139485

Order Date: 11/14/14

Customer Number: 900898
E-ONE, INC

Dealer Number: 900098
E-ONE, INC
1601 SW 37TH AVENUE
OCALA, FL 34474

Model No: AERM-CYC2-SL10
Salesperson: ***

1601 SW 37TH AVENUE
OCALA, FL 34474

Sales Admin: ROUSE,TANGI L

Salescode	Extended Description	Qty	
<u>TESTING COMPLIANCE STANDARD</u>			
1001-0015	The E-ONE supplied components of the vehicle shall meet the requirements of NFPA 1901, 2009 edition.	1	
1001-0016	Post production addendums exist for this order. PPAO / PPRW numbers: PPRW 140277 11/23/15	1	
3090-0001	Hose bed capacity aerial. Provide standard size hose bed.	1	
3090-0003	OAH RESTRICTION. The unit has an overall height restriction. The height is not to be exceeded (unloaded height). 11ft. 6in.	1	
3090-0004	OAL. Unit has no overall length restrictions.	1	
<u>INSPECTIONS AND PENALTIES</u>			
1002-0001	Final inspection trip.	1	
<u>AXLE OPTIONS</u>			
1025-0002	Dana 22I 22,800 lb. front axle.	1	
1025-0023	Meritor RT-50-160 rear tandem axle 54,000 lb. capacity.	1	
1025-0028	Koni shock absorbers for front axle - adjustable.	1	
<u>WHEEL OPTIONS</u>			
1050-0007	Front axle wheel trim kit. Includes stainless steel lug nut covers (chrome plated plastic if applicable) and center cap with E-ONE logo. Note: Center cap will have an inspection port IPO a logo if equipped with Stemco oil seals.	1	
1050-0009	Rear axle (tandem) wheel trim kit. Includes stainless steel lug nut covers (chrome plated plastic if applicable) and center caps with E-ONE logo. E-ONE custom chassis w/steel wheels will have chrome plated plastic lug covers.	1	
1050-0044	Accuride aluminum wheels for front axle (2).	1	
1050-0046	Accuride aluminum wheels for rear axles (8).	1	
<u>TIRE OPTIONS</u>			

Salescode	Extended Description	Qty	
<u>TIRE OPTIONS</u>			
1060-0022	Eight Michelin 12R rear tires with XDN2 mud and snow tread.	1	
1060-0046	Two Michelin 425 tires model XFE for front axle.	1	
1060-0119	RWC AirGuard LED tire pressure monitoring valve stem caps (10) for tandem rear axle applications.	1	
<u>SUSPENSIONS</u>			
1070-0015	Ridewell Dynalastic rear suspension (40-54K) rated equal to the capacity of the axles. Torque box applications only.	1	
<u>BRAKE SYSTEMS</u>			
1100-0006	Parking brake release mounted on the driver's side lower dash.	1	
1100-0008	Brake system air 6X4.	1	
1100-0014	ArvinMeritor 16-1/2" x 7" S-cam brakes with cast brake drums for a tandem rear axle.	1	
1100-0031	Dana ESD225 17" disc brakes for front axle.	1	
1100-0053	G4 Electronic Stability Control with Wabco OnGuard CMS system (6x4). Includes RSC and ATC. Not available on 4x4, commercial chassis or tiller.	1	
<u>AIR SYSTEM OPTIONS</u>			
1110-0000-001	Inlet for air system. Location: driver door jamb.	1	
1110-0002	Air dryer Bendix AD-9.	1	
1110-0006	Air lines nylon.	1	
1110-0026	Air horns recessed in bumper (PR).	1	
<u>SECONDARY BRAKING</u>			
1125-0002	Jacobs engine compression brake.	1	
1125-0023	Transmission to seek second gear when Jacobs engine brake or Telma retarder is engaged. N/A with Trans retarder.	1	
<u>BUMPER TRAYS</u>			
1150-0095	Hinged diamond plate lid for center bumper tray. Includes D-Ring latch and gas shock hold open.	1	
1150-0120	Bumper tray center of bumper with slats 12 inches deep (approx 11 inches to slats).	1	
1150-0128	Notch front bumper tray for speaker/Q2B/radar. Will reduce front hose/equipment load. Center tray only.	1	
<u>BUMPERS</u>			
1160-0014	20" Front Bumper Gravel Shield Extension.	1	

Salescode	Extended Description	Qty	
<u>BUMPERS</u>			
1160-0041	Heavy duty front bumper 10" high with full wrap around. To be painted job color.	1	
1160-0131	1/8" Front Bumper Gravel Shield for heavy duty bumper. Includes 1" turn down around perimeter of HD bumper.	1	
<u>ENGINES & TRANSMISSIONS</u>			
1200-0017	Push-button transmission shift selector.	1	
1200-0021	TransSynd synthetic transmission fluid for EVS 4000.	1	
1200-0096	Electronically limited speed to 60 MPH.	1	
1200-0239	Eng/Trans Cummins ISX12 500HP with EVS4000 transmission. 2013 EPA Compliant.	1	
<u>FRAME ASSEMBLY</u>			
1250-0005	Frame - Torque box for tandem axle RM aerial.	1	
<u>FUEL SYSTEMS</u>			
1350-0012-670	Fuel shut-off valve. Location: one (1) inlet side of OEM fuel filter.	1	
1350-0022	Fuel line hose rubber.	1	
1350-0050	Fuel system 60 gallon saddle tanks.	1	
<u>BATTERIES</u>			
1400-0002	Battery four group 31 1000 CCA.	1	
<u>SEATS</u>			
1510-0003	Seats, Inc. brand 911 cab seats.	1	
1510-0009	Seat color black.	1	
1510-0062	Two man bench centered on rear wall with 911 SCBA backs. Includes angled corners.	1	
1510-0203-147	Bracket SCBA Lifeguard SmartDock Gen2 restraint system. Location: officer's seat.	1	
1510-0203-148	Bracket SCBA Lifeguard SmartDock Gen2 restraint system. Location: rear facing driver's side.	1	
1510-0203-151	Bracket SCBA Lifeguard SmartDock Gen2 restraint system. Location: inboard driver's side rear wall.	1	
1510-0203-152	Bracket SCBA Lifeguard SmartDock Gen2 restraint system. Location: inboard officer's side rear wall.	1	
1510-0203-215	Bracket SCBA Lifeguard SmartDock Gen2 restraint system. Location: rear facing officer's side.	1	
1510-0234	Seat cover material Turnout Tuff.	1	
1510-0279-151	ReadyReach seat belt extender. Location: inboard driver's side rear wall.	1	

Salescode	Extended Description	Qty	
<u>SEATS</u>			
1510-0279-152	ReadyReach seat belt extender. Location: inboard officer's side rear wall.	1	
1510-0281	Driver seat 911Battalion air ride ABTS.	1	
1510-0283	Officer seat to be 911Battalion ABTS fixed SCBA.	1	
1510-0284	Rear facing 911 Battalion ABTS seat with SCBA driver's side.	1	
1510-0285	Rear facing 911 Battalion ABTS seat with SCBA officer's side.	1	
1685-0033	Seating capacity tag of six occupants.	1	
<u>HVAC</u>			
1515-0018	Air conditioning for the Typhoon X, CII X and Quest with roof top mounted condenser.	1	
1515-0053	Controls for heating and air conditioning shall be located in the center dash area. (Lower area on Typhoon and CII with severe duty dash)	1	
1685-0057	Heaters cab rear with covers (PR), and front heater with heat to the feet for the driver and officer.	1	
<u>CAB MODEL</u>			
1520-0008	Cyclone II X medium cab with 58" CA	1	
<u>CAB DOOR OPTIONS</u>			
1550-0003	Rear crew cab doors in the medium position.	1	
1550-0005	Driver and officer cab door windows. Include forward vent windows.	1	
1550-0017	Cab door panels stainless steel.	1	
1550-0024	All cab doors shall have exterior paddle latches.	1	
1550-0027	Front cab door windows to have manual actuation.	1	
1550-0038-659	(4) LED cab step area lighting. Locate each light on each cab door in the inboard position. Lights to be switched with door ajar.	1	
1550-0077	Interior cab door locks - manual. Will have manual actuation from each respective door. Includes barrel style key lock on each exterior cab door.	1	
1550-0084	All cab exterior access doors to have 1250 keyed locks.	1	
1550-0103	Rear crew cab door windows with rear fixed panel. Includes manual roll-down actuation. For use with paddle style door latching.	1	
1550-0178-000-J7	Red/Fluorescent Yellow Green Reflexite V98 chevron "A" stripe on lower cab door panel approx 12" high. Stainless steel door panels only. TyphoonX, CIIX and QST2 only.	1	
<u>CAB BADGE PACKAGE</u>			
1610-0000	Cab and body to have applicable E-ONE logos.	1	
<u>CAB ROOF TYPE</u>			

Salescode	Extended Description	Qty	
<u>CAB ROOF TYPE</u>			
1615-0022	Cab roof to have 12" high split raised rear section with full length center waterway trough. For use with rear mount aerial.	1	
<u>MIRRORS</u>			
1670-0062	Retrac Aerodynamic dual vision chrome west coast style mirrors (PR) mounted on cab doors. Includes remote control and heat for std and convex mirrors and LED marker light.	1	
<u>MISC EXTERIOR CAB OPTIONS</u>			
1550-0009	Fixed rear cab wall narrow windows (pr).	1	
1550-0020	Windows cab side fixed driver's side.	1	
1550-0033	Windows cab side fixed officer's side.	1	
1675-0022	Pair of 18" handrails located just behind driver and officer front door one each side.	1	
1675-0024	Pair of 36" handrails located just behind driver and officer rear door (ALS doors if equipped) one each side.	1	
1675-0030	Mud flaps, front, black with E-ONE logo.	1	
1675-0041	Stainless steel trim belt low on sides of cab.	1	
1675-0047	Rear cab wall to be 3/16" aluminum diamond plate.	1	
1675-0201	Large radius cab wheel well. Includes bolt-on ajustable wheel well trim.	1	
1675-0202	Mounting plate for battery charger receptacle, indicator and air inlet (if applicable). Plate to be removable brushed stainless steel.	1	
<u>CHASSIS OPTIONS</u>			
1680-0007	Drivelines 1810. Required on 1550 lb/ft torque or greater engines.	1	
1680-0008	Tow eyes front painted below bumper/cab (PR).	1	
1680-0012	Tow eyes rear frame painted.	1	
1680-0051	Aerial hydraulic activation system.	1	
1680-0118	Cold Weather Pkg for Cab. Includes fan clutch and additional insulation on the front wall and insulation on rear cab heater hose lines (if equipped).	1	
1680-0250-M58	Diesel Exhaust Fluid (DEF) 5 gallon tank for 2013 EPA engines. Location: left side below rear of cab.	1	
<u>MISC INTERIOR CAB OPTIONS</u>			
1680-0053	Storage below rear bench seat. (1) hinged door on each side of the bench seat.	1	
1685-0001	Cab interior black. Does not include seat color.	1	
1685-0006	Padded sun visors, driver and officer's side overhead.	1	
1685-0008	Control lanyard Y type for air horns.	1	

Salescode	Extended Description	Qty	
MISC INTERIOR CAB OPTIONS			
1685-0112	Integrated Roll Sensor (IRS) for RollTek air bag system.	1	
1685-0113	Integrated roll sensor slave module for RollTek air bag system.	1	
1685-0115	Integrated Belt Pretensioner (IBP) for RollTek air bag system.	6	
1685-0187	Severe duty engine cover, molded polyurethane.	1	
1685-0263	Severe duty dash package. Includes smooth plate alum center and officer side dash and lower kick panels; all painted to match cab interior. Officer cab dash notched for MDT slideout bracket(s).	1	
1685-0285	Cup holder / tray for engine cover painted to match cab interior. Approx 14" wide x 10" long with tapered front corners and cup holders at each rear corner. For use in Typhoon and CII with severe duty engine cover.	1	
1685-0291	4Front air bag system with steering wheel bag, driver knee bag and officer knee bag. Requires RollTek option.	1	
1685-0365	Air ride seat pull down (S4) for RollTek air bag system.	1	
1685-0366	Side Rollover Airbag (SRA) for RollTek air bag system.	4	
ALTERNATOR			
1700-0019	Alternator Niehoff 360 amp (360 amp SAE/320 NFPA rating). Available only on ISX12 and ISX15.	1	
CAB ELECTRICAL OPTIONS			
1750-0009-846	Radio AM/FM CD with weather band located center overhead console offset to driver side.	1	
1750-0010	Radio speakers additional pair. Locate each side rear cab ceiling.	1	
1750-0027	Control push-button switch officer dash for Q2B siren.	1	
1750-0046-195	Cab Headlights. Position: lower.	1	
1750-0059-179-02	Receptacle inlet 20 amp with a Red cover. Location: outside driver's door next to handrail.	1	
1750-0072-592	12 VDC (or 24VDC) electrical outlet in the cab wired battery hot. Location: driver side dash.	1	
1750-0075	English dominant main cab gauge cluster.	1	
1750-0149	Control push-button switch on officer's dash for Q2B siren brake.	1	
1750-0158	Dome Lts Red/White LED. Package includes two lights mounted in the front and two mounted in the rear of the cab. White light wired through door and light assembly switch. Red light through light assembly switch.	1	
1750-0188	DPF regeneration override switch.	1	
1750-0198-A31	Battery charger to be located behind driver's seat.	1	
1750-0215-172	Turn signal Whelen M6 LED arrow amber pair located upper headlight bezel.	1	

Salescode	Extended Description	Qty	
<u>CAB ELECTRICAL OPTIONS</u>			
1750-0283	LED cab headlights. TyphoonX, CIIX and QST2 only.	1	
1750-0343	Battery charger E-ONE LPC 20. 120 volt inlet, 20 amp output.	1	
1750-0423-09X	Programming instructions for auxiliary switch 1 on steering wheel switch pod. Switch function: Front brow light(s). (Requires relay option if lights are not 12v).	1	
1750-0424-09V	Programming instructions for auxiliary switch 2 on steering wheel switch pod. Switch function: Q2B.	1	
1750-0425-09W	Programming instructions for auxiliary switch 3 on steering wheel switch pod. Switch function: Q2B Brake.	1	
1750-0450	Steering wheel with switch pods IPOS. Includes wiper functions, master warning sw, air horn sw, aux brake on/off and (3) aux switches. Required with Typhoon and CII equipped with 4Front. (Requires seporate programming options to activate aux switches)	1	
<u>COOLING PACKAGE</u>			
1800-0013	Cooling system for use with Cyclone II X, Typhoon X, and Quest chassis. For use with 2010/2013 EPA engines. Includes coolant recovery system.	1	
<u>BODY SPEC</u>			
3090-0000	Body Specs - SideStacker aerial with tandem axle. Includes left rear staircase with pocket style drop down step.	1	
<u>BODY COMPT REAR</u>			
3110-0058	Rear of body to have flush un-painted smooth plate body panels to facilitate rear body striping.	1	
<u>PUMP PANELS</u>			
3134-0006	The single gauge panel on the driver's side of the side mount module is to be hinged downward. Includes two (2) cable hold opens, and latches.	1	
3134-0016	Stainless steel driver and officer side pump panels.	1	
3134-0100	Officer side upper pump access panel to be horizontally hinged with diamond plate door. Includes (2) push button latches and (1) hold open device.	1	
<u>PUMP MODULE OPTIONS</u>			
3136-0000-202	Air horn switch at pump panel. Switch to be labeled "Evacuation Alert". Location: driver side pump panel.	1	
3136-0005	The crosslay divider(s) to be notched both ends for Task Force Nozzle.	1	
<u>DOORS</u>			
3300-0007-017	Door single vertical hinged painted. Location(s): R3	1	
3300-0011-005	Door single horizontal hinged lift-up box pan configuration painted. Location(s): L3	1	

Salescode	Extended Description	Qty	
DOORS			
3300-0011-006	Door single horizontal hinged lift-up box pan configuration painted. Location(s): L4	1	
3300-0021-007	Door roll up short (up to 45") with painted finish ROM. Location(s): L5.	1	
3300-0022-003	Door roll up tall (greater than 45") with painted finish ROM. Location(s): L1.	1	
3300-0022-004	Door roll up tall (greater than 45") with painted finish ROM. Location(s): L2.	1	
3300-0022-008	Door roll up tall (greater than 45") with painted finish ROM. Location(s): L6.	1	
3300-0022-015	Door roll up tall (greater than 45") with painted finish ROM. Location(s): R1.	1	
3300-0022-016	Door roll up tall (greater than 45") with painted finish ROM. Location(s): R2.	1	
3300-0164-018	Door double vertical hinged w/rotary latches - painted . Location(s): R4	1	
COVERS			
3305-0001	Cover aluminum (2) piece with recessed handles, SideStacker. Note: This option effects hose bed capacity.	1	
3305-0008-000-02	Vinyl Red crosslay cover with attached side flaps.	1	
3305-0022-000-02	Vinyl rear cover for diamond plate hose bed cover. Color: Red.	1	
AERIAL BODY OPTIONS			
3310-0032	Recessed tubes for (6) pike poles. Not available on HP75 SideStacker.	1	
3310-0061	Crosslay triple (2) 4.25" wide single stack to hold up to 200' of 2.0" DJ (each) and (1) 5.5" wide to hold up to 150'-200' 2.5" DJ. Includes storage pan to rear of crosslays	1	
3310-0069	Rear ladder tunnel doors. Vertically hinged smooth plate to match rear body finish.	1	
3310-0096	Doors for rear master and jack control controls. Doors will match rear body finish.	1	
3310-0291	Jack leg opening covers brushed finish S/S (4) sets. Includes outrigger covers and fixed filler panels.	1	
3310-0300	Compartments driver side HPS105 ladder SideStacker and 300 gallon tank (set up for 42" PPNL for 240" WB medium cab). Includes rescue style extended height compartments and raised rear body for improved angle of departure.	1	
3310-0301	Compartments officer side HPS105 ladder SideStacker with 300 gallon tank. Includes rescue style extended height compartments ahead of wheel well with extended hosebed and raised rear body for improved angle of departure.	1	
3310-0303	Auxiliary jack pad 24X24 (4) with 20 degree formed handle. Includes (4) mounting brackets.	1	
3310-0330	Fuel fill hinged door and fixed panel below door each side to rear of tandem axle to be brushed S/S IPOS. Grain to run horizontal.	1	
SCBA BOTTLE STORAGE			

Salescode	Extended Description	Qty	
<u>SCBA BOTTLE STORAGE</u>			
3320-0018	SCBA Bottle Storage. (8) Fire Shopp SCBA bottle storage with hinged doors with push button latches. (4) officer side and (4) driver side in wheel well area.	1	
3320-0100	Strap, loop style to retain SCBA bottle (EA). Locate one per bottle in each wheel well SCBA storage compartment.	8	
<u>HANDRAILS / STEPS</u>			
3330-0002-050	Slide-out platform, rollerless. Includes chrome grab handle centered on the front face of the platform (includes hand rail as applicable). Located below driver side pump panel.	1	
3330-0115	Intermediate pump panel step officer side with forward tapered corner. Includes (2) lower and (1) upper dual LED lighted CPI folding step and a minimum of (1) handrail as req to meet NFPA. Step lights to be switched thru work light in cab.	1	
<u>MISC BODY OPTIONS</u>			
3340-0077	Body compartment Interiors to have Zolatone gray finish. To include pan of hinged doors and tool compartments (as applicable). Does not include floors if they are dia plt.	1	
3340-0093	Mud flaps, rear, black with E-ONE logo.	1	
3340-0270	The painted aerial body side panels shall be smooth / flush. Applies to SideStacker HB side, panels next to water tank on MM, and upper body sides on RLP.	1	
3340-0895	Smooth plate tandem axle wheel well painted job color. Includes bolt-on composite wheel well liners and bolt-on polished alum fenderettes. Wheel well plates to be flush mounted.	1	
<u>LADDER STORAGE / RACKS</u>			
3365-0013-607	Center mounted ladder tunnel. Ladder rack to hold: (2) PEL-35, PEL-28, PEL-24, PRL-20, PRL-16 and FL-10 (with rubber block feet).	1	
<u>PUMPS</u>			
4005-0016	Hale QMAX 1000-2250 GPM single stage pump.	1	
4005-0033	Rating 2000 GPM	1	
<u>WATER TANK</u>			
4010-0195	300 gallon "T" water tank. UPF Poly III blue fill tower.	1	
<u>PUMP OPTIONS</u>			
4015-0002	Mechanical speed counter for Hale pumps.	1	
4015-0022	Mechanical pump seal - Hale.	1	
4015-0053-198	Steamers to be Flush + 1". Location: driver's side.	1	

Salescode	Extended Description	Qty	
<u>PUMP OPTIONS</u>			
4015-0053-199	Steamers to be Flush + 1". Location: officer's side.	1	
4015-0073	Manual operated master pump drain. The master drain shall be clearly marked and placed in accessible location rearward below running board on driver side or L1 compartment.	1	
4015-0210	Pump cooler with Innovative Control 1/4 turn valve with "T" handle and label.	1	
<u>DISCHARGES AND PRECONNECTS</u>			
4415-0008	1.5" front bumper discharge Akron manual valve.	1	
4415-0012-654	1.5" crosslay with Akron manual valve. Location: crosslay 1 & 2.	2	
4415-0058-655	2.5" Crosslay Akron Manual Valve. Location: crosslay 3.	1	
4415-0161-581	2.5" Left Panel Discharge Akron Manual Valve w/30 Degree Chrome Droop. Location: left side discharge 1.	1	
4415-0161-582	2.5" Left Panel Discharge Akron Manual Valve w/30 Degree Chrome Droop. Location: left side discharge 2.	1	
4415-0164-584	2.5" Right Panel Discharge Akron Manual Valve w/30 Degree Chrome Droop. Location: right side discharge 2.	1	
4415-0178-532	Polished Stainless Steel Swivel Located on Top of Bumper officer's side of center tray for Front Bumper Discharge.	1	
4415-0986-583	4" Right Pump Panel Discharge w/4" Akron Electric Valve with 9323 controller. (Waterous pumps noted location to be forward lower port) Location: right side discharge 1	1	
4415-0994	4" waterway discharge with 4" Akron electric valve with 9323 controller.	1	
<u>DISCHARGE OPTIONS</u>			
4417-0176	Innovative Controls 3/4" bleeder/drain valve include lift lever with ergonomic grip.	9	
4417-0185	Innovative Controls discharge and intake bezels with integral color code and verbiage for side mount pump panel.	1	
<u>GAUGES</u>			
4435-0083	Innovative Controls 10 LED SL series water tank level gauge. On pump panel.	1	
4435-0246	2.5" Innovative Controls stainless steel case pressure gauge (0-400) with color code bezel	9	
4435-0247	4" Innovative Controls stainless steel case master pressure gauges with bezel. Intake 30-0-400, and discharge 0-400.	1	
<u>INTAKES</u>			
4440-0005	2.5" Left Intake Akron Manual Valve.	1	
<u>INTAKE OPTIONS</u>			

Salescode	Extended Description	Qty	
<u>INTAKE OPTIONS</u>			
4445-0009	Intake relief valve, Akron.	1	
<u>TANK PLUMBING</u>			
4450-0010	2" tank fill Akron manual valve.	1	
4450-0022	3" tank to pump Akron manual valve.	1	
<u>MISC PUMP PANEL OPTIONS</u>			
4460-0003	Pump panel tags color coded per NFPA compliance.	1	
<u>PRESSURE GOVERNORS</u>			
4465-0017	FRC PumpBoss pressure governor PBA400. Includes engine monitor gauges.	1	
<u>PUMP CERTIFICATION</u>			
4475-0000	Pump certification 750-2250 GPM	1	
<u>ELECTRICAL SYSTEMS</u>			
5010-0039	V-MUX Electrical system for aerials.	1	
5010-0049	Vehicle data recorder - 2009 NFPA compliant. Includes occupant detection shown in multiplex display. E-ONE chassis only.	1	
5010-0055-649	Vista IV display for V-MUX electrical system. Location: driver's side engine cover.	1	
<u>MISC ELECTRICAL</u>			
5110-0017	Back-up alarm 97 dB.	1	
<u>ELECTRIC CORD REELS</u>			
5130-0002-389	Cord reel electric with 200' of 10/3 yellow cable. Location(s): pump module storage pan officer side.	1	
5130-0022-821	Cord reel rollers mounted through panel. Location(s): officer side pump module in line with reel.	1	
5130-0024-203	Electric cord reel rewind switch. Switch located officer side pump panel.	1	
<u>DOT LIGHTING</u>			
5150-0017	License plate light LED with chrome housing located at the rear of the body.	1	
5150-0026	Marker light LED body/cab package. E-ONE custom cab with aerial ladder, Mid-Mount platform or Bronto bodies only.	1	
5150-0032	Bracket license plate at rear of body.	1	
5150-0129	Whelen M6 series LED horizontal mount tail lights. Includes LED stop/tail, arrow turn and back-up lights individually mounted with weatherproof connectors.	1	

Salescode	Extended Description	Qty	
<u>BREAKER BOXES</u>			
5200-0001-C37	Breaker box 12 place single phase. Includes main breaker. Note: If gen is 6KW or less, main will occupy 2 places leaving 10 available. Locate L1 back wall above jack access panel.	1	
<u>GENERATOR</u>			
5250-0125-128	Generator Harrison 10KW LPG hydraulic. Includes generator control/PTO engage switch and a gauge panel located adjacent to breaker box. Generator location: officer side of open storage area.	1	
<u>GENERATOR TEST</u>			
5255-0001	3rd party generator test with pump.	1	
<u>LIGHT BARS</u>			
5300-0157-035	Whelen Mini-Freedom LED light bars (PR) model FNMINI 24" with clear lenses and MKEZ7 mounts. Location: front cab corners at 20 degree angle.	1	
<u>CAMERAS / INTERCOM</u>			
5350-0070	Voyager back-up camera. Video displays automatically when transmission is in reverse. Camera only - does not include monitor.	1	
5350-0156	FRC ACT 2-way aerial intercom.	1	
5350-0193	Voyager rear facing camera positioned on officer's side front cab corner (approx 31" bottom of camera to bottom of cab) interlocked with right turn signal. Camera only - does not include monitor.	1	
5350-0194	Voyager rear facing camera positioned on driver's side front cab corner (approx 31" bottom of camera to bottom of cab) interlocked with left turn signal. Camera only - does not include monitor.	1	
<u>LIGHTS - COMPARTMENT, STEP & GROUND</u>			
5380-0032	Ground light package LED - large.	1	
5380-0036	Step light package body LED - small.	1	
5380-0253	Compartment light package ROM V4 LED for large bodies. Includes one light per compartment (two if transverse).	1	
<u>LIGHTS - DECK AND SCENE</u>			
5390-0007	Deck/scene light circuit wiring through chassis reverse. Requires rear deck or scene light.	1	
5390-0025	Cab scene lights are to be switched with cab doors in addition to standard.	1	
5390-0073-444	Deck Light - Whelen LED model PFBP12C (PR). Location: (1) each side over rear ladder tunnel.	1	
5390-0087-397	Whelen M6 Linear Super LED scene lights (PR). Switched in cab (lights mtd on the sides of apparatus to be switched separately). Locate (1) each side of cab, rearward of forward doors, up high.	1	

Salescode	Extended Description	Qty	
<u>LIGHTS - DECK AND SCENE</u>			
5390-0088	Crosslay light Whelen PFBP12C LED. Locate to rear of crosslay (SM) and forward of crosslay (TM as applicable). Switched with work light switch in cab.	1	
5390-0170-R88	Whelen M6 Linear Super LED scene light (EA). Switched in cab (lights mtd on the sides of apparatus to be switched separately). Locate front area of hosebed, facing rearward.	1	
<u>LIGHTS - NON-WARNING</u>			
5400-0003	Engine compartment light (EA).	1	
5400-0010	Incandescent pump compartment light (EA).	1	
5400-0092	Weldon pump panel LED light package with (3) lights per side pump panel. Pump panels over 45" may require additional lights. Side mount only.	1	
<u>LIGHTS - QUARTZ</u>			
5450-0115-437	Light Whelen 12 volt Pioneer Plus model PFP1 with brow mount (EA). Includes switch in cab (driver and officer side facing lights switched separately). Location(s): driver and officer side front cab brow.	2	
5450-0261-063	Light Whelen Pioneer model PFP2AC 120V with external bottom raise pole mount. Location(s): officer side back of cab.	1	
5450-0261-064	Light Whelen Pioneer model PFP2AC 120V with external bottom raise pole mount. Location(s): driver side back of cab.	1	
<u>RECEPTACLES</u>			
5470-0001-495	Receptacle twist lock 20A/110V 3 wire NEMA L5-20 with cover plate. Location: driver side rear wheel well offset forward.	1	
5470-0001-498	Receptacle twist lock 20A/110V 3 wire NEMA L5-20 with cover plate. Location: officer side rear wheel well offset forward.	1	
<u>SIRENS</u>			
5500-0011-209	Federal Q2B siren - Pedestal mounted on bumper. Location: driver side front bumper.	1	
5500-0015	Whelen model 295SLSA1 siren with microphone (replaced 295HFSA1).	1	
5500-0024-170	The electronic siren control is to be located on the center overhead.	1	
<u>SPEAKERS</u>			
5510-0018-211	Whelen SA122FMP electronic siren speaker recessed in front bumper. Location: officer side front bumper.	1	
<u>WARNING LIGHT PACKAGES</u>			
5550-0173-535	Whelen M6 Super LED lower level warning light package. Includes (8) red M6R LED light heads and (2) red M2R LED light heads. Locate side facing lights: at forward most position, centered in rear wheel well, and side facing at rear of body in rubrail if equipped.	1	

Salescode	Extended Description	Qty	
<u>WARNING LIGHTS</u>			
5600-0078-290-06	Whelen Super LED beacon (PR) model L31H with Red domes. Location above L2/R2 compartments offset rearward to supplement upper rear warnings.	1	
5600-0078-479-06	Whelen Super LED beacon (PR) model L31H with Red domes. Location rear upper body on aerial style brackets.	1	
5600-0105-170	Hazard (door ajar) light 2" LED. Location: center overhead.	1	
5600-0241-464	Warning light Whelen M6R series Linear Super LED (PR) red. Location: (1) each side of cab down low just ahead of rear doors.	1	
<u>AERIAL MODEL</u>			
6100-0054	Ladder steel 105'. For use with SideStacker body. Includes pinned waterway, left side console with cover, turntable mansaver bars, split steps at tip and jack leg flood lights.	1	
<u>AERIAL HYDRAULIC SYSTEM OPTIONS</u>			
6150-0003-216	Gauge aerial hydraulic oil level. Electronic display to be located on pump operator's panel.	1	
<u>MONITORS</u>			
6300-0048	Wireless control for TFT Monitor on aerial. Includes (1) transmitter and stainless steel mounting bracket.	1	
6300-0070	Monitor TFT Typhoon RC electric w/extended range 1000GPM for ladder. Includes shut off valve at tip (VUM) with 2.5" aux discharge valve. Includes tip and base controls. Monitor has a powder coated silver finish. Requires high flow W/W relief vlv.	1	
<u>WATERWAY OPTIONS</u>			
6350-0005	Rear 4" NST waterway inlet for rear mounted aerals. Includes chrome cap.	1	
6350-0063	Relief valve Hale P40 for aerial waterway IPOS. Required with tip vlv option. For use with four section aerial only.	1	
6350-0067	2.5" Innovative Controls stainless steel case pressure gauge (0-400) with color code bezel. Locate next to waterway inlet	1	
<u>AERIAL EQUIPMENT</u>			
6500-0019-138	Axe bracket mounted on aerial. For use with a 6 lb. axe only. Location: left side fly section.	1	
6500-0067	PAC TRAC postive locking bracket (PR) for 8' pike pole on ladder includes stop plate to prevent the pole from sliding. location: right side of base horizontally mounted behind sign plate.	1	
6500-0111	Bolt-on ladder tip. Steel aerals only.	1	
6500-0117	Lifting eyes each side on bolt-on ladder tip. Rating is 250 lbs ea / 500 lbs pr.	1	
<u>AERIAL WARNING LIGHTS</u>			

Salescode	Extended Description	Qty	
<u>AERIAL WARNING LIGHTS</u>			
6550-0002	Outrigger warning lights (4) LED. Truck-Lite model 91R.	1	
6550-0048	Whelen VTC6R Vertex Super-LED lights at ladder tip (PR). Red with clear lenses and chrome bezels. Switched with aerial master.	1	
<u>AERIAL LIGHTING</u>			
6560-0041	Whelen LED model PFBP12C at base (PR).	1	
6560-0080-000-03	Ladder climbing lights Luma Bar Pathfinder LED strip for 4 section aerial (one side). Color: Blue.	1	
6560-0104-231	Light Whelen Pioneer Plus 12V model PFP1P1 with PBAPEDD pedestal mount. Switched at light head and base console. Location(s): left side tip.	1	
6560-0105-232	Light Whelen Pioneer Plus 120V model PFP1AP1 with PBAPEDA pedestal mount. Requires 110 volt twist lock receptacle at tip option. Location(s): right side tip.	1	
<u>MISC AERIAL ELECTRICAL</u>			
6570-0015	110V/20A twist lock receptacle at tip.	1	
6570-0024	Laser jack pad spotting lights (4).	1	
<u>AERIAL LADDER BRACKETS</u>			
6600-0002-248	Roof ladder bracket J style mount. Locate outside base section for a PRL-14 on left side of base section. Available on HP75/78, HP100, and HP95.	1	
<u>SIGN PLATES</u>			
6750-0001-000-39	Aerial sign plates 16 x 144 (PR). Available on HP95, HP100L and HP100P only. Does not include lettering. Color: Job Color	1	
<u>AERIAL CONTROLS</u>			
6850-0025	Advanced Aerial Control System - Ladder. Includes monitor stow / deploy, cradle alignment It and display with flowmeter.	1	
6850-0027	Ladder tip controls. For use with AACS only.	1	
<u>AERIAL TESTING</u>			
6900-0000	Aerial flow test - 3rd party.	1	
6900-0002	Aerial 2009 NFPA Certification.	1	
<u>GROUND LADDERS</u>			
7800-0007	Alco-Lite PRL-14' roof ladder.	1	
7800-0010	Alco-Lite PRL-16' roof ladder.	1	
7800-0016	Alco-Lite PEL-24' 2-section extension ladder.	1	
7800-0021	Alco-Lite PEL-28' extension ladder.	1	

Salescode	Extended Description	Qty	
<u>GROUND LADDERS</u>			
7800-0024	Alco-Lite PEL-35' extension ladder.	2	
7800-0038	Alco-Lite PRL-20' roof ladder.	1	
7800-0078	Alco-Lite FL-10, 10' folding ladder without shoes and handles.	1	
<u>MISC LOOSE EQUIPMENT</u>			
7900-0014	DOT Required Drive Away Kit - Kit includes three (3) triangular warning reflectors with carrying case. This kit is for the end user and is to remain with the truck.	1	
<u>EXTERIOR PAINT</u>			
8100-0064	Cab paint break - standard with dip to grille. Break is 31.5" inches below the drip rail on Typhoon X and CII X cabs. Pre-07' emission Typhoon cab break is 33.5" below the drip rail.	1	
8100-0084	All applicable pump/pre-connect application modules are to have a job color finish. Includes upper and lower pump modules, crosswalk module and/or speedlay/pre-connect module (as applicable). Rear mounted body/pump module to be painted job color.	1	
8100-0116	Rear body surface to have a sanded finish (not painted job color). Includes hinged doors that do not have discrete sales codes and removable panels.	1	
8100-0176-000-17	Paint E-ONE chassis cab - Sikkens paint. Color: FLNA3225E-1 Red.	1	
8100-0177-000-18	Paint cab Sikkens two-tone. Upper area of cab to be painted FLNA4006 White.	1	
8100-0183-000-17	Paint Body - Large - For Aerials, T/A Tankers/Wetsides, Rear Mounts and Rescues. Sikkens paint. Color: FLNA3225E-1 Red.	1	
8100-0222	Paint all roll up door header plate(s) job color.	1	
8100-0354	Paint lift cylinders, extension cylinders and upper turntable steelwork primary job color (does not apply to TT deck).	1	
8100-0483	Paint bolt-on tip orange IPOS. Includes nozzle guard (if equipped). Steel aerials only.	1	
8100-0484-000-18	Paint aerial ladder (Sikkens). Steel aerials only. Color: FLNA4006 White.	1	
<u>INTERIOR PAINT</u>			
8150-0007	The interior of the cab to be painted Zolatone black.	1	
<u>LETTERING</u>			

Salescode	Extended Description	Qty	
LETTERING			
8200-0103	Demo graphics package - Aerial Ladder (2015). Includes 16" Sign Gold style demo logo on front cab doors, .75" Sign Gold stripe around perimeter of sign plates (with scrolls in corners), large E-ONE Sign Gold logo at each end of sign plates and ladder model name (HP75 LADDER, HP78 LADDER, METRO 100 LADDER, HP100 LADDER, CR100 LADDER, HPS105 LADDER OR CR137 LADDER) in Sign Gold lettering on sign plates (Perpetua bold font - sized to fit). All Sign Gold material to have black border.	1	
STRIPING			
8200-0016	White reflective tape on (4) outriggers.	1	
8300-0016	Paint Break Sign Gold Chassis Stripe - 3/4" Wide - Black, Gold, Black. To be located above existing paint break.	1	
8300-0026-000-12	Scotchlite stripe 1" located 1" above and below existing stripe. Color: White.	1	
8300-0027-334-12	NFPA Scotchlite 4" wide hockey stripe, straight across front and may contour as it transitions from cab to body on each side. Color: White. Location: bottom of stripe flush with top of bumper and straight back.	1	
8300-0034-000-12	Scotchlite stripe 2" located 1" above existing stripe. Color: White.	1	
8300-0035	Striping Instructions: Striping to kick up on L2/R2 doors to midway up on upper body sides. Stripes to be interlocking style at transition.	1	
8300-0042	White rubrail scotchlite insert.	1	
8300-0273-000-J7	Chevron "A" style 6" Reflexite V98 striping on front bumper. Colors to be Red/Fluorescent Yellow Green.	1	
8300-0274-000-J7	Chevron "A" style 6" Reflexite V98 striping full width on rear of body. Includes rear facing extrusions, panels and doors. Colors to be Red/Fluorescent Yellow Green.	1	
GRAPHICS			
8400-0033	Logo E-ONE (PR) on aerial lift cylinder. Logo to be sign gold material approx 14" long located midway along outward surface of cylinder.	1	
8400-0047	Logos E-ONE (PR) on side cab window. Logo to be gray "etched" look centered on glass.	1	
WARRANTY / STANDARD & EXTENDED			
9100-0000	Standard 1 Year Warranty.	1	
9100-0003	Lifetime Frame Warranty.	1	
9100-0004	10 Year/100,000 Mile Structural Warranty for Alum Cab / Body - Statement of Warranty.	1	
9100-0005	10 Year Stainless Steel Plumbing Warranty - Statement of Warranty.	1	
9100-0007	20 Year Aerial Device Structural Warranty - Integrity Limited Warranty.	1	
9100-0019	10 Year Limited Paint and Perforation Warranty - For Sikkens Paint.	1	

Salescode	Extended Description	Qty	
<u>WARRANTY / STANDARD & EXTENDED</u>			
9100-0079	5 Year Limited Aerial Paint and Perforation Warranty - For Sikkens Paint.	1	
<u>SUPPORT, DELIVERY, INSPECTIONS AND MANUALS</u>			
9300-0009	Manuals, Operator and Service CD-ROM.	1	
9300-0016	Approval Drawings-Standard.	1	
9300-0316	Fire Apparatus Safety Guide published by FAMA, latest edition.	1	