M# ITEM SELECTION DESC

CUSTOMER: Eagle FD Model 1 FINAL

UNIT ID: B42, B43, B45
DESIGN: Model 1
DATE: 10/1/2025
GSO #: 25103-25105





		FORD F550 (SUPPLIED)	CUSTOMER SUPPLIED FORD F550
9	CHASSIS		N/C REF ONLY
		FULL REPAINT - SOLID	FULL CHASSIS REPAINT TO DEPT SPECIFICATIONS, MATCH FLEET, CHASSIS TO BE REPAINTED SILVER OVER LIME 2
			TONE (SEE PROOFS, DEPT TO PROVIDE PAINT CODES & APPROVE SPRAY OUTS AND PAINT BREAK LOCATION
1	CHASSIS FINISH		
	BUCKSTOP	BUCKSTOP SRW	KIT INSTALLATION
1	INSTALL	CONVERSION INSTALL	
		BUCKSTOP S3 FORD	BUCKSTOP STAGE 3 SRW FORD F550 CONVERSION KIT
			335/80R20 CONTINTENTAL MPT81 (5), 11"X20" REVERSIBLE DOT ALUM WHEELS (5), HIGH ARCH FENDER FLARES,
			OUTBACK BUMPER (WIDE), 3.5" SUSP. LIFT, SPEEDO, ABS, TRACTION CONTROL CALIBRATION MODULE /
	SUSPENSION,		CORRECTION, RADFLO REMOTE RESERVOIR TUNED 2.5" SHAFT SHOCKS
1	WHEEL & TIRE		
		BUCKSTOP [SRW] (INC W/KIT	BUCKSTOP CONV KIT FRONT BUMPER - CONFIGURED AS FOLLOWS
		S1 OR S3) FORD F550	F175WOB BUMPER, W/ OUTBACK GRILL GAURD (PC HAMMER BLACK), DITCH LIGHT CUTOUTS, WINCH MOUNTING
			PLATE ASSY (BUILT EXTRA WIDE FOR TIRE COVERAGE, FLUSH FIT W/ FLARES)
			(N/C REF ONLY \$ INC W/ SRW CONVERION #F235S2 OR #F235S3)
1	BUMPER		
		AFTERMARKET, DUAL STEP,	OEDRO 6" RUNNING BOARDS - FORD, BOLT ON, STEEL NERF BAR, DOUBLE STAIR DESIGN, BLACK POWDERCOAT
1	CAB STEPS	FORD F550	
		FACTORY + INSTALL TO BODY	FACTORY CAMERA - SUPPIED W/ CHASSIS, MOUNT TO BODY & ROUTE HARNESS TO HEAD UNIT / PROGRAM (CHASSIS
1	BACK UP CAM	/ HEAD UNIT (BODY)	SUPPLIED W/ CAMERA & UPFITTER KIT)
		CUSTOM	STRIPING PER DEPT SPECS / MATCH FLEET & DETAILS BELOW: PINSTRIPE AT PAINT BREAK
			6" BLACK / CHARCOAL BODY STRIPE W TRACER
2	STRIPING		STRIPE ALONG BOTTOM OF CAB, BOTTOM 1/3 OF BODY [NO CHECK UP])
		LIME / RED	6" NFPA CHEVRON, REAR APRON OF BODY, LIME & RED, ORALITE GHOST STRIPE PRISM
2	REAR CHEVRON		N/C REF ONLY \$ INC W/ STRIPING LINE
			DEPT LOGO ON FRONT CAB DOORS, EA. SIDE: (EAGLE FD MALTESE SHIELD LOGO)
2	DOOR LOGOS	STYLE [SPEC]	N/C REF ONLY \$ INC W/ STRIPING LINE
		UNIT ID - ROOF	UNIT ID ON CAB ROOF, PLACED REAR OF LIGHTBAR, CONTRASTING COLOR FROM CHASSIS FINISH
		CONTRASTING COLOR FROM	N/C REF ONLY \$ INC W/ STRIPING LINE
2	ROOF UNIT ID	CHASSIS FINISH	

	1	LINIT ID DEAD CAR DOOD /EA	UNITED ON DEAD CAD DOODS FA CIDE. (D++ UNITED)
١ .	0.05.10.17.10	UNIT ID REAR CAB DOOR (EA	UNIT ID ON REAR CAB DOORS, EA. SIDE: (B** UNIT ID)
2	SIDE UNIT ID	SIDE) [SPEC STYLE]	N/C REF ONLY \$ INC W/ STRIPING LINE
		UNIT ID BACKSIDE [SPEC	UNIT ID ON REAR OF BODY OR BEDRAIL
		STYLE / PLACEMENT]	(B** UNIT ID IN BLACK REFLECTIVE, ON R3 COMPARTMENT
2	REAR UNIT ID		N/C REF ONLY \$ INC W/ STRIPING LINE
	FRONT BUMPER ID	CUSTOM	FRONT BUMPER ID PLATE FASTENED TO FRONT BUMPER IN PLACE OF LICENSE PLATE, POWDERCOATED JOB COLOR:
2	PLATE		FOR FRONT UNIT ID TO BE APPLIED TO
		MODEL 1 (ALT)	HIGHWAY PRODUCTS BODY ASSY 9061-951 DESIGNED IN PARTNERSHIP FOR SWEV, CONFIGURED AS FOLLOWS:
			- 8' X 9'6" FLATBED SQUARE CORNER
			- NOTCHED FRONT CORNERS
			- INSET BOX (HOSE COMPARTMENT) IN SILL
			- CROSS FRAME L1 / R1 COMPARTMENT "HORSESHOE" CENTER @ 12", SWING DOOR (HINGED CAB SIDE) W/ GAS
			SHOCK, ADJ SHELF, 2 LOWER SECTION WING ADJ SHELVES, D RING HANDLE (BLACK)
			- (2) L2 & R2 LIFT DOOR BOXES, 56"WX29"HX18"D, VERTICAL LIFT SINGLE DOOR W/ GAS SHOCK (2), ADJ SHELF, D
			RING HANDLE (BLACK)
			- (1) R3 LIFT DOOR BOX, 22"WX29"HX18"D, VERTICAL LIFT SINGLE DOOR W/ GAS SHOCK (2), ADJ SHELF, D RING
			HANDLE, DRAWER IN R3 COMPARTMENT BASE EXTEND TO OFFICER SIDE
			REAR APRON W/ FULL WIDTH STEP
3	BODY ASSY		
		MODEL 1 (REELS FORWARD,	STANDARD MODEL 1 TOPSIDE STORAGE CONFIGURATION AS FOLLOWS:
		COFFIN CF)	****-*** DRIVER SIDE: HEX PUNCH, SMOOTH OUTER FACE, 41.5"WX12"HX18"D, PC BLACK
			****-*** OFFICER SIDE: HEX PUNCH, SMOOTH OUTER FACE, 71.5"WX12"HX18"D, PC BLACK
	BODY TOPSIDE		****-*** COFFIN BOX, TOP LIFT BETWEEN HOSE REELS OVER L1/R1 TRANSVERSE, HINGED CAB SIDE, T HANDLE, W/
3	STORAGE		GAS SHOCKS + SHOCK SW, PC BLACK, 60W"X12D"X12"H
		POWDERCOATED - CHASSIS	BODY TO BE POWDERCOATED TO MATCH CHASSIS COLOR - CODE: (TBD, LIME)
		COLOR	FLATBED, TOPSIDE BOXES IN/ OUT, DOORS, APRON, ETC.
3	BODY FINISH		BLACK ACCENTS BLACK BK62, BLACK TOPSIDE STORAGE
		N/A	REPAINT BODY - SWEV WARRANTY INTERNAL MATCH CHASSIS
			EXTERNAL SURFACES ONLY
8	BODY FINISH		PER BREAKDOWN W/ EAGLE & NWAB
		STORAGE DRAWERS IN L1/R1	ADD X1EA PULL OUT DRAWER TO (EA SIDE) BOTTOM OF L1 & R1, WITH SHELF SET TO ENCLOSE TOP - 10" DEEP. PC
3	L1/R1 DRAWERS	LOWER SECTIONS 1/SIDE	BLACK BK62
3	GRAB STRAPS	YES	GRAB STRAPS INSTALLED TO L2, R2, AND R3 VERTICAL LIFT DOORS
		SWEV HITCH STEP / SHACKLE	SWEV HITCH STEP / REC MOUNT SHACKLE COMBO
			FLIP STEP ON DROP, 2.5" HITCH MOUNT, ACCEPTS 2" HITCH SHACKLE, DOUBLE PINS, W/ INTEGRATED LIGHT
3	HITCH STEP		,
		SPITZ LIFT CRANE 4' MANUAL	SPITZ LIFT 4' FOLDING BOOM MANUAL CRANE, 20' MIL SPEC WEBBING W/ 1.25 TON HOOK LATCH (FOR HOISTING
3	SPITZ LIFT HOIST		SPARE TIRE ON OR OFF TOPSIDE OF BODY)
<u> </u>	10	I.	STATE THE GRONDIT TO DIDE OF BODT)

		HOIST MOUNT	POST MAST ADAPTER 26" AND 6" VERTICAL UNIVERSAL MOUNT BASE PEDASTAL INSTALLED TO FRONT INSIDE CORNER
		TIGIGI FIGGIVI	OF OS BASKET AND R2 COMPARTMENT W/ STRUCTRUAL PLATE SUPPORT TO SPREAD LOAD.
	SPITZ LIFT MOUNT		900 LB. RATED CAPACITY
3	& SUPPORT		300 LB. HATLD CALACITI
١Ů	4 301 1 OK1	2 HANDLES PLACEMENT TBD	2 GRAB HANDLES, 12"+/- EA. KNURLED BAR W/ RED REFLECTIVE INSERTS, 90 DEG STANCHIONS, PLACEMENT
3	HANDLE OPTIONS	REAR, 12"	LOCATION TBD / DEPT TO SPECIFY
		BODY - SIDE ZICO (EA SIDE)	MANUAL PULL OUT STEP ZICO PS-8-5. TO ACCESS TO TOPSIDE
3	BODY SIDE STEPS		LOCATED REAR BOTTOM EDGE OF CROSSFRAME BOX
	BATT CHARGER	KUSSMAUL CHIEF 4012	KUSSMAUL CHIEF SERIES 4012 BATTERY CHARGER
		KUSSMAUL CHIEF OLED, 20A,	KUSSMAUL 20A SUPER AUTO EJECT, W/ CHIEF OLED STATUS CENTER, MOUNTED ON D SIDE FENDER SKIRT IN FRONT
4	AUTO EJECT	YW	OF REAR WHEEL, YELLOW COVER, VERTICAL MOUNT
	AUTO EJECT	AUTO EJECT SHROUD	SHROUD FOR BACKSIDE OF AUTOEJECT (UNDERBODY) TO PROTECT FROM ELEMENTS (THROWN ROCK, MUD, ETC)
	SHROUD		ALUM
		SUNSTRIP - COMP LIGHT EA	FRC SUNSTRIP VERTICAL COMPARTMENT LIGHTING
		SIDE OPENING	AUTO ON W/ DOOR OPENING - GAS SHOCK SWITCH - AS FOLLOWS
			L1 SIDE: 45", R1 SIDE: 45",
	COMPARTMENT		L1/R1 CENTER SECTION: 45" ACROSS TOP CENTER HAT STIFFENERS - CENTERED
	LIGHTING (MODEL		L2: (2) 27",
	1 STD BODY		R2 (2) 27",
4	LAYOUT)		R3 (2) 27"
	GROUND	CAB DOOR POSITIONS & 2	ROM 6" & 12" GROUND LIGHTS - 2 X 12" UNDER REAR APRON, 1 X 6" (4) UNDER EACH CAB DOOR POSITION -
4	LIGHTING	UNDER APRON	ILLUMINATE GROUND. AUTO ON X ALL W/ CAB DOOR OPEN OR SWITCH
		STANDARD	9" FRC SUNSTRIP LIGHTS - TOPSIDE WORK
		5 X 9" SUNSTRIP SPLIT	1 PER BASKE T/ TOPSIDE COFFIN TO ILLUMINATE CONTENTS
		BETWEEN BASKETS / STEP /	1 PER BASKET / TOPSIDE COFFIN FRONT INSIDE WALL TO ILLUMINATE TOPSIDE (W/ SHROUD)
	TOPSIDE WORK	CATWALK / TOPSIDE	1 ON BENT EDGE OF CATWALK TO ILLUMINATE STEP AREA (W/SHROUD)
4	LIGHTING		SWITCHED AT PUMP PANEL (TOPSIDE WORK) ROCKER SW.
		DUAL PODS (WHELEN NANO)	WHELEN NANO PIONEER POD LIGHT ON SWEV ANGLE PEDASTAL BASE MOUNTED OUTER CORNERS OF REAR WORK
	REAR WORK		AREA, REAR FACING, AUTO ON W/ REVERSE OR DUAL SWITCHED (CAB + PUMP PANEL) W/ OFFSET ANGLE MOUNT
4	LIGHTING		FOR WHELEN NP6BBLED POD LIGHT BK62
		POD - WHELEN NANO BODY	WHELEN NANO PIONEER POD LIGHT MOUNTED TO HOSE REEL FRAME / ROLLER ASSY ARM,
		FRONT CORNER DRIVER	DRIVER CORNER OF BODY AT 45 DEG, W/ OFFSET ANGLE MOUNT FOR WHELEN NP6BBLED POD LIGHT BK62
	DRIVER SCENE		MOUNT TO HOSE REEL FRAME
4	LIGHTING		
	DRIVER SCENE	DRIVER SCENE HI VIZ	HIVIZ FT-WL-X-9-FT-B
4	LIGHTING		MOUNTED TO FORWARD CORNER ON GUSSET OF DRIVER SIDE BASKET, TOPSIDE
		POD - WHELEN NANO BODY	WHELEN NANO PIONEER POD LIGHT MOUNTED TO HOSE REEL FRAME / ROLLER ASSY ARM,
		FRONT CORNER OFFICER	OFFICER CORNER OF BODY AT 45 DEG, W/ OFFSET ANGLE MOUNT FOR WHELEN NP6BBLED POD LIGHT BK62
	OFFICER SCENE		MOUNT TO HOSE REEL FRAME
4	LIGHTING		

	OFFICER SCENE	OFFICER SCENE HI VIZ	HIVIZ FT-WL-X-9-FT-B
4	LIGHTING		MOUNTED TO FORWARD CORNER ON GUSSET OF OFFICER SIDE BASKET, TOPSIDE
		2 PER WHEEL POSITION	2 LED ROCK LIGHTS PER WHEEL WELL, FORWARD AND BACK OF EACH TIRE, ANGLED INWARDS
		ANGLED TO CENTER	(8 TOTAL) ROCK LIGHT KIT (ALL SWITCHED TOGETHER) WIRED TO CENCOM / SWITCHED AT CENCOM
4	ROCK LIGHTS		(,
	DOOR AJAR	CAB & BODY AUDIBLE +	CAB DOORS SWITCHED THRU OBDII INTEGRATION, COMPARTMENTS AT GAS SHOCK SWITCH - AUDIBLE ALARM
4	SYSTEM	VISUAL	BUZZER & RED LIGHT - INSTALLED TO CONSOLE
		DUAL INSTALL, DEPT	INSTALL DEPT SUPPLIED RADIOS UTILIZING DEPT SUPPLIED ANTENNA BASES + COAX KITS - DUAL RADIO INSTALL TO
		SUPPLIED RADIOS	HAVIS (DOES NOT INCLUDE PROGRAMMING)
			DEPT TO SPECIFY ANTENNA PLACEMENT AND PROVIDE RADIO MODEL #(S):
			MIDPOINT LIGHTBAR & BACK OF CAB:
			GPS CENTERED, ANTENNA TO EITHER SIDE EQUALLY SPACED W/ ADEQUATE OFFSET TO EDGE OF CAB FOR EQUAL
			BROADCAST/SHEET METAL
			INSTALL DEPT SUPPLIED INTERNET MODEM / CRADLEPOINT
	RADIO		
4	INSTALLATION		DEPT TO SUPPLY ALL INFORMATION & EQUIPMENT TO COMPLETE
	FRONT FOG	AMBER 6" RND	6" AMBER FOG LIGHTS INSTALLED IN 6" CUTOUTS IN BUMPER - SWITCHED AT CCTL7 "FOG LIGHTS" PUSH BUTTON
4	LIGHTING		
		CAB & PUMP PANEL	DRIVER, OFFICER, AND REAR WORK LIGHTS SWITCHED FROM CAB OR PUMP PANEL, TOPSIDE WORK LIGHTS
			SWITCHED PANEL ONLY
	SCENE LIGHT		ALL OTHER LIGHTING FUNCTIONS SWITCHED FROM CENCOM SYSTEM CONTROLLER IN CAB
4	SWITCHING		PUMP PANEL SCENE LIGHT ROCKER SWITCH COVERS ETCHED FOR FUNCTION
		RED ETCHED ROCKER	ROCKER SWITCH FOR MASTER POWER BATT DISCONNECT AT HAVIS CONSOLE - TRIGGER SOLENOID TO DISCONNECT
			QTY 1 - ACTUATOR COVER - RED, ETCHED (MASTER POWER)
			QTY 1 - MOMENTARY WATERPROOF ROCKER SWITCH, ON/OFF (V2D1-AX0B)
			QTY 1 - SWEV CUSTOM ROCKER SWITCH GUARD BEZEL (WATERJET AND FORM / RS)
4	MASTER BATTERY		
	CORE	STANDARD	CORE ELECTRICAL, SOLENOID(S), FUSE BLOCKS, BREAKERS, MISC. WIRE / TERMINALS
	ELECTRICAL,		
	FUSING,		
4	SOLENOID, ETC.		
		CENCOM CORE WCX C399 &	WHELEN CORE WCX - C399 CENTOM CORE SYSTEM - MOUNTED DS UNDER/ BEHIND SEAT
	SYSTEM /	CCTL7 21& SLIDE	CCTL7 WECANX SYSTEM CONTROLLER, 21 PUSH BUTTON AND 4 POS SLIDE SWITCH, PA MIC & CABLE
5	CONTROLLER	CONTROLLER	
		CEM 16, EXPANDED	WHELEN 16 OUTPUT, 4 INPUT WECANX EXPANSION MODULE (3)
5	EXPANSION		1 UNDER HOOD FOR FRONT ELECTRONICS, 2 IN PUMP PANEL FOR REAR ELECTRONICS

		1	
		STANDARD, SA315P	WHELEN SA315P 123 DB SIREN SPEAKER & SPEAKER BRACKET SAK1 UNIV. L ANGLE
			SPEAKER MOUNTED TO FRONT BUMPER
			CHANGE ORDER: REMOVED SAK1 BACK TO STOCKROOM & INSTALLED SAK61AD PER BELOW
5	SIREN SPEAKER		
	SIREN SPEAKER	CUSTOM, CHANGE ORDER	RE INSTALL SIREN SPEAKER FROM FRONT BUMPER TO BEHIND GRILL UTILIZING SUPER DUTY VEH SPEC MOUNT
5	MOUNT		
		HOWLER SYSTEM DUAL SPKR	WHELEN HOWLER LOW FREQUENCY SIREN SPEAKER SYSTEM (DUAL) W/ UNIVERSAL MOUNT KIT (2)
5	HOWLER SYSTEM	& AMP / UNIV BKTS	(-)
		WHELEN LIBERTY II WCX	WHELEN LIBERTY II WECAN X 54" CTR DDDD LIGHTBAR, MOUNTED FRONT CAB
		(FORD CHASSIS)	DUO R/W FRONT, R/A REAR, R/W CORNER MODULES, LEFT & RIGHT ALLEY LIGHTS, TAKEDOWNS, W/ MKAJ94
5	LIGHTBAR	(1 0112 011110010)	MOUNTING STRAP KIT FOR FORD F SERIES
<u> </u>	LIGITIDAN	LED/IR 795H	OPTICOM INSTALLED IN LIGHTBAR. PROGRAMMED TO 3RD SLIDE POSITION
5	ОРТІСОМ	LED/IR 79311	795H, GTT IR OPTICOM, IJ795HT LIBERTY II EMITTER PREWIRE W/TD
	FRONT GRILL	ION "T" R/W DUO, CLR LENS	WHELEN ION T-SERIES DUO TLI2D (CLR) RED/WHITE, FRONT GRILL WARNING LIGHT - MOUNTED TO BRUSH GUARD
_ ا		ION 1 R/W DOO, CLR LENS	` ' ' · · · · · · · · · · · · · · · · ·
5	WARNINGS	LONG WITH DUA OV	UPRIGHTS OR TO GRILL FACE (DEPT SPEC PLACEMENT) *QTY 2
_	FRONT GRILL	ION "T" BLACK	WHELEN ION T-SERIES BEZEL, BLACK TIONFB
5	LIGHT BEZELS		*QTY 2
	FRONT BUMPER	M6 R/W DUO, CLR LENS	WHELEN M6 M6DD (CLR) RED, FRONT LOWER WARNING LIGHT - MOUNTED TO LOWER OUTSIDE ASPECTS OF
5	WARNINGS		BUMPER, FORWARD FACING *QTY 2
	FRONT BUMPER	M6 BLACK	WHELEN M6 BEZEL, BLACK M6FB
5	WARNING BEZELS		*QTY 2
	FRONT BUMPER	M6 SHROUD	WHELEN M6 WARNING SHROUD INSTALLED TO FRONT LOWER WARNINGS TO PROTECT FROM SURFACE IMPACT
	WARNING		
5	SHROUD GUARDS		
		M2 RED, CLR LENS	WHELEN M2 SERIES LIGHTHEAD ML2RC (CLR) RED, INTERSECTION WARNING LIGHT, MOUNTED TO FRONT FENDER
	INTERSECTION		OVER TIRE EA SIDE
5	WARNINGS		*QTY 2
	INTERSECTION	M2 BLACK	WHELEN M2 BEZEL, BLACK M2FB
5	WARNING BEZELS		*QTY 2
		M2 RED, CLR LENS	WHELEN M2 SERIES LIGHTHEAD ML2RC (CLR) RED, MIDSHIP WARNING LIGHT, MOUNTED TO BEDRAIL OVER TIRE EA
	MIDSHIP		SIDE
5	WARNINGS		*QTY 2
	MIDSHIP	M2 BLACK	WHELEN M2 BEZEL, BLACK M2FB
5	WARNING BEZELS		*QTY 2
		M6 V, RED, COMBO LIGHT	WHELEN M6 M6VRC (CLR) RED, UPPER WARNING LIGHT, MOUNTED TO UPPER OUTSIDE BODY CORNERS
	REAR UPPER	PER. SCENE	*OTY 2
5	WARNING LIGHTS		
	REAR UPPER	M6 BLACK	WHELEN M6 BEZEL, BLACK M6FB
	WARNING LIGHT		*QTY 2
5	BEZELS		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
	PLALLO		

		M2 RED, CLR LENS	WHELEN M2 SERIES LIGHTHEAD ML2RC (CLR) RED, REAR LOWER WARNING LIGHT, MOUNTED TO LOWER REAR
	REAR LOWER	, -	APRON / BEDRAIL OUTSIDES
5	WARNING LIGHTS		*OTY 2
	REAR LOWER	M2 BLACK	WHELEN M2 BEZEL, BLACK M2FB
	WARNING LIGHT		*QTY 2
5	BEZELS		
		DOMINATOR T/A	WHELEN TAL65 SURFACE MOUNT TRAFFIC ADIVSOR (36") W/ TACTL5 CONTROLLER (INSTALLED TO HAVIS) TRAFFIC
	OTHER /		ADVISOR MOUNTED ON REAR FACING TOP LIP EDGE OF TANK TOPSIDE WALKWAY
5	SPECIALTY		
		STD HARNESSES	PROGRAM PATTERNS AND FUNTIONS TO DEPT SPECS:
			CYCLE PRESS FOR SIREN FUNCTIONS
			POSS CYCLE PRESS FOR LIGHT FUNCTIONS (ie: 1= DUO OF M6, 2= PREV & TAKEDOWNS, 3= PREV, PRE, & ALL
			LIGHTBAR WHITE) REPLICATED AS STATED ACROSS OTHER FUNCTIONS TO MAXIMIZE LAYOUT
			LIGHTING PACKAGE INSTALLATION AND WIRING - INCLUDES HARNESSES
			COREHEXP16: J5 & J6 EXPANSION OUTPUT HARNESS, COREHCAN: CORE CEM DATA COMM CABLE J7, COREHGND:
			CORE - GROUND HARNESS
			WHE C399SP; WHELEN SCANPORT OBDII INT MODULE
5	PROGRAMMING		WITE GOSSOI . WITELEN SCANT ON OBDITINI PIODOLE
ا ا	FROOKAMMINO	WARN 16.5 TI, W/ SYNTHETIC	WARN 97740 16.5 TI, 16,500 WINCH W/ SYNTHETIC CABLE
6	WINCH	CABLE	WARN 97740 10.5 II, 10,500 WINCH W/ STIVITIETIC CABLE
⊢ ٽ	WINCH	FACTOR 55 ULTRAHOOK	FACTOR 55 ULTRAHOOK (RED) INSTALLED IN PLACE OF FACTORY WARN WINCH HOOK
6	ACCESSORIES	TACTOR 33 GETRATIOOR	TACTOR 33 OF TRAITOOK (RED) INSTALLED IN PLACE OF TACTOR I WARN WINCITTIOOK
⊢	TOW HOOK /	2" HITCH MNT SHACKLE	INCLUDE 2" HITCH MOUNTED SHACKLE. 15 TON, RED
6	SHACKLE	2 THICH MINI SHACKLE	INGLODE 2 THIGH PIOCHTED SHAGKEE. 13 TON, NED
—	OTACKEE	FULL CATWALK - DP OVERLAY	3/16 ALUM DMND TREAD PLATE TOPSIDE WALKWAY COVERING TOP OF TANK, CORNERS NOTCHED FOR FILL TOWERS,
	TOPSIDE	W/ TREAD SURFACE BLACK	POWDERCOATED GRIP TEXTURE BLACK - MOUNTED TO TANK MOUNT BLOCKS
6	WALKWAY	GRIP PC	TOWNERCOATED ONLY TEXTONE BEACK-PRODUTED TO TANK PRODUIT BEOCKS
\vdash	TOPSIDE TIRE	TRIPLE LOOPS & Y STRAP TO	3 D RING MOUNTS ATTACHED TO TOPSIDE CATWALK OVERLAY SPACED AROUND SPARE, Y STRAP TO FASTEN TIRE
6	MOUNT	CATWALK	DOWN TO TOPSIDE FROM D RINGS
⊢ <u> </u>	1100111	30" FORD 13.3" VSW HAVIS	30" FORD 13.3" VSW CONSOLE, FLAT, CONFIGURED AS FOLLOWS:
		FLAT CONSOLE ASSY	CENCOM CORE FACEPLATE
		LAN GONGOLE AGO!	RADIO FACEPLATE(S) *SPECIFY MODEL(S)*
			SELF ADJ DUAL DUPHOLDER
			OTY 2, ADJ SIDE MOUNT ARMRESTS
			2 12V ROUND, USB-C/USB-A & 3 ROCKER BLANKS
			USB-C/USB-A POWER PORT
			MISC. 9" FILLER PLATES (A/N)
			MISC. 3.3" FILLER PLATES (A/N)
			5" ACC POCKET, 4.8"D
			13" DOCUMENT POCKET, 9" D
6	CENTER CONSOLE		1.5" FILLER W/ ROCKER BLANK
	DEMIEW COMPORE		1.3 FILLEN W/ NOOKEN DEANK

	BULLETPOINT	SINGLE BALL MNT (CONSOLE)	BULLETPOINT 20MM BALL MOUNT ON UNIVERSAL 2 HOLE FLAT PLATE - MOUNT TO HAVIS FOR ACCESSORY
6	MOUNT OPTIONS	, ,	ATTACHMENT
		DEPT SUPPLIED 12V	INSTALL DEPT SUPPLIED PORTABLE RADIO CHARGER(S). WIRE POWER TO CONSTANT 12V POWER ,
	PORTABLE RADIO	CHARGERS - MOUNT & WIRE	WIRE IN 4 GANG CIG LIGHTER BANK TO BACK OF CONSOLE FOR CONNECTION POINT - FUSED IN HAVIS
	CHARGERS -		
6	MOUNT & WIRE		
		MODEL 1 ALT1	UPF RECTANGULAR POLY TANK PER DWG 715-1064
			500 GAL, STD SUMP / DRAIN / SUCTION / VENT
			10 GAL INTEGRAL FOAM CELL
			FOAM CELL X2 NPT FEMALE
			2" OVERFLOW VENT BOTT
			TAB MOUNTING F/B W/ STIFFENER
			BLOCK MOUNTING TABS X5 (58X3X1)
			FOAM AND WATER FILL TOWERS ON DS EDGE, INLINE, WATER FILL ON TANK MIDLINE FORWARD OF FOAM CELL
			PORT NPT F PLACEMENT TBD PER PLUMBING ASSY LAYOUT(S)
			2" SLEEVE FOR TOPSIDE PLUMBING INTERNALLY ADDED & APPROVED
			FRONT MOUNTS CHANGED TO UNDERBODY STYLE
			CHANGED TO REC MOUNTS FROM TS 1" BLOCKS FOR HEIGHT EQUALIZAITON
7	POLY TANK		
		AKRON BRASS SWING OUT	ALL VALVES 1" + TO BE AKRON BRASS 8800 OR 8600 SERIES REBUILDABLE BRASS VALVES W/ SS BALL
7	VALVE TYPE		
7	FOAM CELL	YES	FOAM CELL INCLUDED IN STANDARD MODEL 1 POLY TANK (10 GAL)
		FOAMPRO	FOAMPRO 1601 FOAM SYSTEM, INCLUDING: FOAM PUMP, CONTROL MODULE, CHECK VALVE W/ INJ PORT + DRAIN,
			SIDE MOUNT FOAM LEVEL SWITCH, SYSTEM & SPEC PLACARDS, AND EXTERNAL FLUSH KIT (3/4") (THRU STEP FACE)
			FOAM PUMP INSTALLED UNDER PLUMBING STEP
			CHECK VALVE TO SEPARATE OS PLUMBING FROM TF, FLOWMETER ON OS PAST CHECK VALVE
7	FOAM SYSTEM		
		FOAMPRO	FOAMPRO 1601 FOAM SYSTEM, INCLUDING: FOAM PUMP, CONTROL MODULE, CHECK VALVE W/ INJ PORT + DRAIN,
			SIDE MOUNT FOAM LEVEL SWITCH, SYSTEM & SPEC PLACARDS, AND EXTERNAL FLUSH KIT (3/4") (THRU STEP FACE)
	FOAM SYSTEM		FOAM PUMP INSTALLED UNDER PLUMBING STEP
	INSTALL, SUPPLY		
	& DRAIN		CHECK VALVE TO SEPARATE OS PLUMBING FROM TF, FLOWMETER ON OS PAST CHECK VALVE
7	PLUMBING		
		REEL 1 (TOPSIDE, DUAL)	MODEL: EF4038-17-18 (1 X LT, 1 X RT)
			12V 227 MOTOR, 1" 90 DEGREE SUPER SWIVEL JOINT W/ VITON, 1" MALE NPSH RISER, BEARING MOUNTED STRAP
			BRAKE, FH-330 TOP WIND, PAINT BLACK. (NO HOSE)
			CAPACITY: 125' 1" / 200' 3/4"
7	HOSE REEL MODEL		MOUNTED TO TOP OF BODY L1&L2 / R1&R2 COMPARTMENTS

		CUSTOM	SUB STANDARD SPOOL STYLE ROLLERS TO FULLY ENCLOSED C2 W/ 1/2" DIA ROLLER & 3.5" SIDE ROLLER PAIR
		COSTOM	f/EF4038-17-18
_	LIGOT BOLLEDO		
7	HOSE ROLLERS		MOUNTING BRACKETS FIOR 9939.1062
		IN CAB + BEDRAIL DUAL	PUSH BUTTON MOMENTARY REWIND BUTTONS BUTTON MOUNTED TO BEDRAIL INLINE W/ HOSE REELS (EA SIDE)
		TOPSIDE	BLACK BEZELS ETCHED "REWIND"
			HOSE REEL REWINDS IN CAB - MOMENTARY ROCKER SWITCHES ETCHED LEFT REEL REWIND & RIGHT REEL REWIND
l _	HOSE REEL		
7	REWIND(S)	<u> </u>	
	HOSE REEL	TOPSIDE DUAL	PLUMBING TO TOPSIDE HOSE REELS (D+O SIDES, ON TOP OF LH/RH COMPARTMENTS) ROUTED THROUGH TANK /
	DISCHARGE		SLEEVE, SPLIT TO EACH REEL, VALVED IN REEL BASE AREA W/ AKR 8810 (TS HANDLE)
7	PLUMBING		
		DARLEY 1-1/2AGE24K 3.17	DARLEY 1-1/2AGE 24K PUMP (3.17 RATIO)
		RATIO	HIGH PRESSURE, LOW VOLUME, GEAR DRIVEN, ENGINE MOUNTED
			KUBOTA D902 DIESEL 24HP, LIQUID COOLED
			120 GPM @ 150 PSI
			NO-DIS-HEAD, DC: ASSY - FLANGE, 2.0 NPT 3/8-16N (4) ON 2.5 SQ
			ALUMINUM ALLOY CASING
			ALUMINUM ALLOY GEAR CASE AND ENGINE ADAPTER
			BRONZE IMPELLER AND WEAR RINGS
			STAINLESS STEEL IMPELLER SHAFT
			MECHANICAL SEAL
			HEAT-TREATED ALLOY STEEL HELICAL GEARS
			BALL BEARING CONSTRUCTION
7	PUMP		2" NPT SUCTION
		24K REMOTE OIL	REMOTE OIL FILTER AND DRAIN KIT
			INCLUDED W/ 24K DIESEL PUMPS, N/C (REF ONLY)
7	PUMP REMOTE OIL		DRAIN LINES ROUTED FOR EASE OF USE / SERVICE
	PUMP FUEL	CHASSIS DIESEL - 24K	UTILIZE CHASSIS DIESEL FUEL TANK FOR PUMP FUEL SOURCE (SUPPLY + RETURN TAPS)
7	SOURCE		
		DARLEY DIGITROL+ PANEL 24K	*UPGRADE*
			DARLEY PUMP CONTROLS STD FOR DIESEL PUMP (24K): DIGITROL - UPGRADE TO DIGITROL+ FOR MAIN PANEL:
			ALL FEATURES OF DIGITROL STD
			THROTTLE TO PRESSURE FEATURE
			LOW OIL PRESSURE AUTO SHUTDOWN
	PUMP CONTROL		LOSS OF WATER AUTO SHUTDOWN
7	SYSTEM		
		DARLEY DIGITROL+ AUX	DARLEY SECONDARY DIGITROL+ PUMP PANEL W/ 30' HARNESS
		PANEL	PANEL TO BE INTEGRATED TO HAVIS CONSOLE AND MIRROR ALL CONTROLS OF REAR DIGITROL+ PANEL
7	DUAL CONTROLS		

		STEP OVER PLUMBING	OS CORNER DECK MOUNT STEP OVER PLUMBING, NOTCHED FOR PLUMBING, WATERJET CUT AND FORMED .188"
		(ENCLOSED) 2	3003 DIAMOND PLATE TOP STEP, WITH .190" 5052 SIDE WALL SUPPORT
			ACCESS DOOR ON FRONT OF STEP HINGED W/ SOUTCHCO C2 LATCH (BLACK) TO ALLOW FOR SERVICE
7	TOPSIDE ACCESS		
		SWEV INTERNAL BOX	SWEV STANDARD PUMP PANEL BOX, BLACK POWDERCOAT - REMOVEABLE FACE
			BOX TO ACCOMMODATE ALL PUMP / WORK AREA CONTROLS, TANK FILL MINI NAVIGATOR
	PUMP PANEL BOX		ADDED EXPANSION PANEL TO CONTAIN FOAM PRO CONTROLS & FRONT DISCHARGE + PRECONNECT VALVE
7	OPTIONS		CONTROLS
	PUMP PANEL FACE	FACE 1 - DIGITROL	SEAWESTERN PUMP PANEL FACE #1 (DARLEY DIGITROL) BLACK FINISH
7	OPTIONS		ETCHED: LOGO
		FRC TANKVISION PRO 400	LED WATER DISPLAY, TANKVISION PRO 400, PRIMARY: INSTALLED TO PUMP PANEL, TIED TO PUMP IGN POWER
7	GAUGE	WATER	
		FRC TANKVISION WATER	LED WATER DISPLAY, TANKVISION CAB MINI, REMOTE: INSTALLED TO CONSOLE, TIED TO PUMP IGN POWER
7	WATER GAUGE	(MINI)	
		, . ,	LED WATER DISPLAY, MAXVISION, LARGE, REMOTE: INSTALLED TO SIDES OF BODY UPPER FORWARD DOOR FRAME
	AUXILLARY WATER		(EA SIDE) L1 / R1 (2), TIED TO PUMP IGN POWER
7	LEVEL GAUGE		
		DARLEY FLUIDLESS 12V	DARLEY FLUIDLESS 12V PRIMER - HEAVY DUTY AP01707, PUSH BUTTON ELECTRIC CONTROL - MOUNT UNDER BODY,
_		(PUSH BUTTON ELECTRIC	DIGITROL WIRING CONTROL PANEL INTERFACE INCLUDED FOR PANEL(S)
7	PRIMER	VERSION)	
	PRIMER	DARLEY FLUIDLESS 12V	INSTALLATION AND PLUMBING FOR DARLEY AP00960 OR AP01707 PRIMER
l _	PLUMBING /		
7	INSTALL	OULD TAKE O 4 (OU DI LINADIA)	A 4/9 A OF DUMP, TANK TO DUMP A QUOTION BUILT DUMPING ACCEMPLY
	TANK BUMB 0	2" INTAKE, 2-1/2" PLUMBING	1-1/2 AGE PUMP. TANK TO PUMP & SUCTION INLET PLUMBING ASSEMBLY
	TANK - PUMP &	(1-1/2AGE) STD INTAKE TEE	2" MNPT PUMP INTAKE, INCREASED TO 2.5" AND DROOPED TO INLET PLUMBING, 2.5" VALVES, FNH SWIVEL
7	SUCTION INLET ASSY		(SCREENED), TANK - PUMP LINKAGE CONTROLLED, VALVE SUPPORTS, ETCHED BEZELS
⊢ ′		1-1/2AGE OUTLET T	1-1/2 AGE PUMP, INITIAL DISTRIBUTION DISCHARGE PLUMBING ASSY, 2" MNPT PUMP OUTLET, INC TO 2.5 SCHED 10
		1-1/2AGE OUTLETT	SS, DIST TO D (1.5 VIC) AND O (2.5 VIC) DC ASSYS
			33, DIST TO D (1.3 VIO) AND O (2.3 VIO) DC A3313
			ADD T ON INITIAL DISCHARGE STRAIGHT OUT OF PUMP OUTLET: FOR DEPT TO FLOOD DC PLUMBING IN CASE OF
			PRIMER FAILURE FROM EXTERNAL SOURCE
	REAR DISCHARGE		COPE THREAD X VIC STRAIGHT PLUMBING BEFORE VIC & DROP, INCLUDE + INSTALL 1.5" CAP & CHAIN
7	ASSY		SOLE TIME BY THE SHIP LET BING BET ONE TICK BROT, INCLUDE THOMBE IN CONTROL
		TANK FILL LOWER CORNER	DS DISCHARGE ASSY 2 (TANK FILL - ELECTRIC) FROM MAIN DIST T ASSY, TO TANK FILL PORT (BELOW FOAM CELL -
	DRIVER DECK		BEHIND PUMP) W/ AKRON 8615 VALVE + ELECTRIC ACTUATOR
7	DISCHARGE ASSY		VALVE CONTROLLED BY DUAL MINI NAVIGATORS AT PUMP PANEL & IN CAB
<u> </u>			

		STACKED 1.5 DC ASSY (FOAMPRO)	OS DISCHARGE ASSY 2 (STACKED CORNER DC + CROSS DROP & CORNER VERT TO PC: ACCOMODATES FOAMPRO 1601) FROM MAIN DS T ASSY, TO OFFICER DISCARGES & TOPSIDE PRECONNECT, W/ DROP THROUGH DECK SURFACE
			(TO REEL(S), FRONT DC, ETC)
			STAINLESS SCHED 10 PLUMBING W/ AKRON VALVES (1.5" 8815), VALVE SUPPORTS & LABELS
	OFFICER DECK		UTILIZE BLEEDER VALVE & PLUMBING ORDERED FOR SUCTION VALVE FOR MAIN LOWER DC IN STACK, ROUTE FROM
7	DISCHARGE ASSY		OUTLET FLANGE TO APRON (34BV)
		DISCHARGE BLEEDERS	TAP AND INSTALL BLEEDER LINES PAST OUTLET OF VALVE FLANGES:
			PRECONNECT INLINE BEHIND SHROUD
			LOWER CORNER DC (REMOVE OUTLET FLANGE ORDERED ON COMPLETE VALVE AND INSTALL ELKHART 25583001 1.5
	DISCHARGE		MNH FLANGE UNIBODY SERIES (INTERCHANGEABLE) TAP BLEEDER LINE IN DRAIN PORT AND DROP THRU DECK
7	BLEEDERS	OINIOLE DEAD. DEAD DEOL	ALLOPTEMED TO LEMOTH OF FROM TOP OF TOPOLOGIPE PAGENTS
		SINGLE REAR - REAR DECK	SHORTENED TO LENGTH OF FRONT OF OS TOPSIDE BASKET*
		VALVE	TOPSIDE PRECONNECT TOP OF TANK OS EDGE, MOUNTED TO TANK TOP WALKWAY, EXTENDING OVER LOWER
			PLUMBING SHROUD TO STEP SURFACE VERTICAL PLUMBING FROM DISCHARGE ASSEMBLY, VALVED 1.5 AKR 8615 W/ ELECTRIC ACTUATOR & MINI
			NAVIGATOR (PUMP PANEL)
			PLUMBING THRU REAR FACE OF PRECONNECT PLUMBING SHROUD, BELOW PRECONNECT TRAY
			TRAY TO BE POWDERCOATED BLACK W/ HINGED LID & FLAP COVER AT REAR
	TOPSIDE		BLEEDER LINE FROM VALVE OUTLET FLANGE TO SNUBBER VALVE (APRON)
7	PRECONNECT(S)		BELEDER LINE FROM VALVE GOTLEFF ENROE TO SNOBBER VALVE (AFROM)
	FRONT	SINGLE - ELECTRIC VALVE	FRONT 1.5" DISCHARGE THROUGH BUMPER FACE, ELECTRONIC VALVE CONTROL (NAVIGATOR MINI, AT PUMP PANEL)
7	DISCHARGE(S)		,
		MASTER DRAIN	CLASS 1 MASTER DRAIN VALVE - ALL LOW POINT DRAINS IN PUMP AND PLUMBING TIED TO DRAIN. OPEN/ CLOSE
7	MASTER DRAIN		WHEEL TO BE MOUNTED TO APRON
		CUSTOM	ALL VALVE FUNCTIONS TO BE LABELED,
7	VALVE LABELING		HALE 34BV TO BE LABELED AS 2X BLEEDER, 1X DRAIN, 1X FOAM SUPPLY: PER TRUCK
	2.5 PLUG(S)	QTY 1	2.5 NST M PLUG W/CHAIN RL, CHROME - INSTALLED TO SUCTION INLET
	CHROME		
	1.5" CAP(S)	QTY 3	1.5 NST F CAP W/ CHAIN, RL CHROME - INSTALLED TO 1.5" DISCHARGES (QTY 3)
7	CHROME		
7	HARD SUCTION	2.5 X BODY LENGTH (2) NH	QTY 2 2.5" SPIRAL SUCTION HOSES PROVIDED AND INSTALLED IN HOSE BOX, COUPLED 2.5" NH - APPROX 10' L (EA)
8	FULL WIDTH STEP	FULL WIDTH STEP	MISSED AND CLARIFIED, FULL W STEP FOR REAR APRON
	STRAINER	2.5 BARREL STRAINER W/ F.V.	PROVIDED BARREL STRAINER WITH INTEGRATED FOOT VALVE, 2.5" FNH RIGID, ANODIZED ALUM
		OTHER	DEPT SPECIFIED BOOSTER HOSE: PARKER 821FR-12-BLK PUSH LOK FIRE RESISTANT COVERED HOSE, 250-350 PSI NPSH
8	BOOSTER HOSE		**SHIP LOOSE & UNCOUPLED**

		2X DRIP TORCH	C&S SUPPLY DRIP TORCH 1.25 GAL, INCLUDED (QTY 2)
8	DRIP TORCHES		
	DRIP TORCH	DUAL MOUNT	DUAL DRIP TORCH MOUNT, DEPT TO SPECIFY PLACEMENT: SHIP LOOSE
8	MOUNTS		
		S&H NZ-TT-NP (DUAL)	DEPT REQUESTED BOOSTER NOZZLES
	BOOSTER		(2) USFS FORESTER NOZZLES 3/16, 1" NPSH
8	NOZZLE(S)		S&H NZ-TT-NP
	PAC MOUNT -	HANDLELOK (DUAL)	BOOSTER NOZZLE MOUNT, TO FRONT OF BODY, PACT 1004 (2)
	BOOSTER		
8	NOZZLE(S)		
		1 PAIR	ZICO WILDLAND COMPLIANT WHEEL CHOCK, AC-32W (PAIR)
8	WHEEL CHOCKS		SHIP LOOSE
	WHEEL CHOCK	HORIZONTAL MNT 1 PAIR	HORIZONTAL HOLDER FOR AC-32W (SHIP LOOSE) (QTY 2)
8	MOUNTS		SHIP LOOSE
8	TRANSPORT HPI	TRANSPORT TO/FROM HPI	TRANSPORT TO AND FROM HPI FOR BODY INSTALLATION
	TRANSPORT	TRANSPORT TO/FROM	TRANSPORT TO AND FROM BUCKSTOP TRUCKWARE FOR FACTORY SRW CONVERSION KIT INSTALLATION
8	BUCKSTOP	BUCKSTOP	
	INTERNAL	SWEV DESIGN ENGINEERING	SWEV INTERNAL DESIGN AND ENGINEERING (HRLY)
8	ENGINEERING		
		HPI DESIGN ENGINEERING	HPI, ENGINEERING - BODY DESIGN & EDITS (12 HRS)
8	HPI ENGINEERING	(*HR=12)	
		AT SWEV (N/C)	FINAL INSPECTION AND DELIVERY TO CUSTOMER AT SWEV YAKIMA, WA
8	DELIVERY		

